


LumiCloud™ Collection CARRA – VEGA



Spec by:

Agency:

Project Name:

Type of Project:

Notes:



IP22
RATED



LIGHTING PERFORMANCE*

	Output	Size					
		2' x 2'	2' x 4'	4' x 4'	8' x 4'	10' x 6'	12' x 8'
Power consumption (Watts)	Premium	32W	72W	162W	360W	700W	1140W
Delivered output (Lumens)		671 lm	1510 lm	3398 lm	7551 lm	14683 lm	23912 lm

Based on 6,500K CCT

ORDERING CODE

TLS	LC	CR	VG	Rating
Product	Model	Engine		
TLS	LumiCloud LC	Carra CR	Vega VG	Indoor IN Outdoor OUT

Size	Frame	Mounting	Frame color	RGBW65K	P	SA	LS
				CCT	Output*	Control	Diffuser
2' x 2' 2x2	Frameless squared corner SQ	Recessed RD	Black BL	RGBW (6500K) RGBW65K	Premium (563 lm/sq) ³ P	Stand Alone SA	LightTex Silent LS
2' x 4' 2x4	Frameless rounded corner RO	Surface SF	White WH				
4' x 4' 4x4		Suspended SP	Clear Anodized CA				
8' x 4' 8x4		T-bar ¹ TB	Silver ² NS				
10' x 6' 10x6		Wall Surface WLS					
12' x 8' 12x8		Wall Recessed WLR					

¹ Not for rounded corners

² Only for rounded corners




³ Lm/sq are calculated at LED source

TECHNICAL SPECIFICATIONS

■ Diffuser

Light Tex Silent	
Material	100 % Polyester
Weight	172 gr/m2 (16 gr/ft2)
Fire classification	NFPA-701, B1, EN 13501-1, B-s1, d0
Transmission rate	37%
CCT shift	0-50K (see table page 4)
NRC	0.82

■ Frame color

Material	Aluminum		
Standard colors	Black 	White 	Clear Anodized 

Note: Custom colors are available for LumiCloud Bespoke model

■ Lighting

Ingress protection	IP65 - IP22 (indoor)
CRI	~ 90 (white LED)
LM80 *	> 150,000 hours
Operating temperature	-30 °C TO 80 °C


Note: *LM80 Test is only applicable to white pixels.

Warranty*	5-year limited warranty for LED
-----------	---------------------------------


* Warranty Terms and Conditions at www.tls-led.com/warranty

FRAME


■ Frameless square corner (SQ)




FLS 2125-V2



■ Frameless rounded corners (RO)




FLS 2125-V2




SIZES


2'x2'




2'x4'




4'x4'




8'x4'



10'x6'



12'x8'



Note: Custom dimensions are available with LumiCloud™ Bespoke model.

■ Weight

Size	2'x2'	2'x4'	4'x4'	8'x4'	10'x6'	12'x8'
Kg	13	17	22	34	60	72
Lbs	28	38	49	74	133	154

Variations may occur but should not exceed indicated values.


LIGHTING PERFORMANCE AND EFFICIENCY

■ CCT Shifting

Output	CCT
	6,500K
Premium	6,545

■ Foot Candle per height


*Below dimensions are based on Premium Light Tex Silent



Note: Results are simulated based on 10' x 16' room & Reflection factors C70% W77% & F20% ,
other measurements available on requests.
Multiple panels will influence the foot candle.


MOUNTING OPTIONS

Recessed (RD)




- Cavity to be 1/8" (3mm) over nominal
- Cavity to be minimum 7" (177.8mm) deep

Surface (SF)




Suspended (SP)



- Hooks to existing ceiling installed by others


T-bar (TB)



Note: Parts reference numbers are available upon request.

CONTROL

■ Stand alone (SA)



■ Electrical

Driver models	HLG-60-24A, HLG-100-24A, HLG-150-24A, HLG-240-24A, HLG-320-24A
Input voltage	90-277 V AC, 47-63 HZ
Output voltage	21-24 V DC