


LumiSky™ Lite AURORA



Spec by:

Agency:

Project Name:

Type of Project:

Notes:



LIGHTING PERFORMANCE FOR 2'X2'*

	Output	Grid Configuration (2'x2' panel)**					
		1 x 1	2 x 1	2 x 2	2 x 3	3 x 3	5 x 10
Power consumption (Watts)	Premium	44W	88W	176W	264W	396W	2200W
Delivered output (Lumens)		1383 lm	2765 lm	5531 lm	8296 lm	12444 lm	69135 lm

* Power Consumption and Delivered output values are based on 6500K CCT

** See Configuration examples on page 5

ORDERING CODE

TLS	LSL Product	AU Engine	Size	Nº panels horizontal				Nº panels vertical				Application
TLS	LumiSky Lite LSL	Aurora AU	2'x2' 2x2 2'x4' 2x4 4'x4' 4x4 6'x6' 6x6	1	1H	6	6H	1	1V	6	6V	Ceiling CL
				2	2H	7	7H	2	2V	7	7V	Wall WL
				3	3H	8	8H	3	3V	8	8V	
				4	4H	9	9H	4	4V	9	9V	
				5	5H	10	10H	5	5V	10	10V	
				Custom CS				Custom CS				

Mounting	Frame color	CCT	Output*	Control	Diffuser
Suspended Threaded Rods SPT	Black BL	4000K 40K	Premium (688.8 lm/sqft)* P	DMX by TLS DMXT	LightTex Silent LS
Suspended Aircraft cables SPA	White WH	6500K 65K		DMX by others DMXO	LightTex Media LM
Wall semi-recessed WL	Silver NS				
	RAL RAL				

* Lm/sqft are calculated at LED source

LIGHTING PERFORMANCE FOR 2'X4'*

	Output	Grid Configuration (2'x4' panel)**					
		1 x 1	2 x 1	2 x 2	2 x 3	3 x 3	5 x 10
Power consumption (Watts)	Premium	88W	176W	352W	528W	792W	4400W
Delivered output (Lumens)		2765 lm	5531 lm	11062 lm	16592 lm	24889 lm	138270 lm

* Power Consumption and Delivered output values are based on 6500K CCT

** See Configuration examples on page 6

LIGHTING PERFORMANCE FOR 4'X4'*

	Output	Grid Configuration (4'x4' panel)**					
		1 x 1	2 x 1	2 x 2	2 x 3	3 x 3	5 x 10
Power consumption (Watts)	Premium	176W	352W	704W	1056W	1584W	8800W
Delivered output (Lumens)		5531 lm	11062 lm	22123 lm	33185 lm	49777 lm	276540 lm

* Power Consumption and Delivered output values are based on 6500K CCT

** See Configuration examples on page 5

LIGHTING PERFORMANCE FOR 6'X6'*

	Output	Grid Configuration (6'x6' panel)**					
		1 x 1	2 x 1	2 x 2	2 x 3	3 x 3	5 x 10
Power consumption (Watts)	Premium	422.4W	844.8W	1690W	2534W	3801.6W	21120W
Delivered output (Lumens)		13273.92 lm	26548 lm	53096 lm	79644 lm	119465.28 lm	663696 lm

* Power Consumption and Delivered output values are based on 6500K CCT

** See Configuration examples on page 5

TECHNICAL SPECIFICATIONS

■ Diffuser

	Light Tex Silent	LightTex Media
Material	100 % Polyester	100 % Polyester
Weight	172 gr/m2 (16 gr/ft2)	172 gr/m2 (16 gr/ft2)
Fire classification	NFPA-701, B1, EN 13501-1, B-s1, d0	NFPA-701, B1, EN 13501-1, B-s1, d0
Transmission rate	37%	N/A
CCT shift	0-50K	N/A
NRC	0.82	N/A

■ Frame color

Material	Aluminum			
Standard colors	Black 	White 	Silver 	RAL 

■ Lighting

Ingress protection	IP22 (indoor)
CRI	~ 90 (white LED)
LM80 *	> 150,000 hours
Operating temperature	-30 °C TO 80 °C



Note: *LM80 Test is only applicable to white pixels.

Warranty*	5-year limited warranty for LED
------------------	---------------------------------


* See warranty terms and conditions at www.tls-led.com/warranty

STRUCTURE

■ Size 2'x2'/4'x4'/6'x6'





SIDE VIEW




FRONT VIEW

■ Size 2'x4'



SIDE VIEW



FRONT VIEW

■ Standard Dimension







Dimension	2'x2'	2'x4'	4'x4'	6'x6'
A	27.87"	27.87"	53.76"	79.69"
B	27.87"	53.78"	53.76"	79.69"

■ Standard Weight

Size	2'x2'	2'x4'	4'x4'	6'x6'
Kg	19.5	28	36	63
Lbs	20.95	61.73	79.37	138.9

CONFIGURATIONS







■ Size 2'x2'/4'x4'/6'x6'



CUSTOM CONFIGURATIONS ARE
ALSO AVAILABLE UPON REQUEST.

CONFIGURATIONS


■ Size 2' x 4'




CUSTOM CONFIGURATIONS ARE
ALSO AVAILABLE UPON REQUEST.

MOUNTING OPTIONS


■ Suspended with Aircraft Cables




■ Suspended with Threaded Rods



■ Wall recessed




■ Wall semi-recessed




Note: Parts reference numbers are available upon request.

CONTROL

■ DMX by TLS (DMXT)




■ DMX by others (DMXO)







■ Electrical

Driver models	HLG-60-15A, HLG-100-15A, HLG-150-15A, HLG-240-15A, HLG-320-15A
Input voltage	90-305 V AC, 47-63 HZ
Output voltage	14-15 V DC

INSPIRATIONAL CEILINGS



LumiSky Lite offers a collection of inspirational designs—each available for use or as a starting point. Custom images can also be applied for a fully tailored result.



INSPIRATIONAL WALLS



LumiSky Lite offers a collection of inspirational designs—each available for use or as a starting point. Custom images can also be applied for a fully tailored result.

